

INTERACTIVE UPS GS1000



Product Feature

- Specially designed for personal computer with multi functions
- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR
- Green Power Function for energy saving
- DC Start Function
- Auto restart while AC recovery
- Compact size, Light Weight
- Provides AC Overload protection

Product Form Type

Product Form Type	GS1000
Capacity	1000 VA / 600 W
INPUT	
Voltage	220Vac / 230 Vac
Voltage Range	140-290Vac / 140 - 300 Vac
Frequency Range	>40Hz (autosensing)
OUTPUT	
AC Voltage Regulation (Batt.mode)	220Vac / 230Vac±10%
Frequency Range (Batt. Mode)	50Hz±1Hz or 60Hz±1Hz
Transfer Time	Typical 4-8ms, 13 ms max
Waveform (Batt.mode)	Simulated Sine Wave
EFFICIENCY	
Battery Voltage	24V
Battery Number	7AH*2
Charge Current	1.0 A
INDICATORS	
AC Mode	Green LED lighting
Battery Mode	Yellow LED flash
Fault	Red LED lighting
PROTECTION	
Full Protection	Short circuit, Overload , Overcharge and overdischarge protection
ALARM	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Fault	Continuously sounding
PHYSICAL	
Approx , Dimension D X W X H (mm)	345 x 123 x 189
Approx. Net Weight (kg)	8.7
OPERATING ENVIROMENT	
Humidity	0-90 % RH @ 0- 40°C (non-condensing)
Noise Level	Less than 40dB
MANAGEMENT	
Communitacion port	For Choice (USB&RJ45)